

SAFETY DATA SHEET

SILOCK® PROFESSIONAL

625°F BLACK RTV SILICONE

1. Product & Company Identification

1.1 Product Details

Odour:

Colour:

Product name: 625°F Black RTV Silicone Physical form: Paste Acetic Acid Black CAS No.: Mixture

1.2 Company Details

Manufacturer: Silock Technical Inc. Address: Nevada 89102 USA

2. Hazards Identification	
Hazard Pictogram	
	CK®
Signal Word: Warning	NIAI
Classification	INAL
COLUTION	
Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2
<u>Hazard Statement</u> H315 - Causes skin irritation. H319 - Causes serious eye irritation. Precautionary Statement – Prevention	
P264 - Wash thoroughly after handling.	
P280 - Wear protective gloves/protective clothing/ey	e protection/face protection.
Precautionary Statement – Response P302 + P352 - IF ON SKIN: Wash with plenty of soap an P332 + P313 - If skin irritation occurs: Get medical adv P305 + P351 + P338 - IF IN EYES: Rinse cautiously with v contact lenses, if present and easy to do. Continue rin P337 + P313 - If eye irritation persists: Get medical adv	rice/attention. vater for several minutes. Remove nsing.

: 02 REV : 15th Aug 2018 DATE

WEBSITE: WWW.SILOCK.COM.MY

K TECHNICAL INC.

SAFETY DATA SHEET

S

IH ADDRESS: NEVADA 89102 USA.

ck Techinical Inc. is an ISO 9001 certified co 993 - 2020 Silock Techinical Inc. All rights re

SILOCK® PROFESSIONAL

625°F BLACK RTV SILICONE

Precautionary Statement - Storage No precautionary statement. Precautionary Statement - Disposal No precautionary statement.

OI

3. Composition / Hazardous Components			
<u>Chemical Name</u>	CAS No.	<u>WT%</u>	
Titanium dioxide	13463-67-7	< 5%	
Methyltris(methylethylketoxime)silane	22984-54-9	< 10 %	
Treated Fume Silica	68611-44-9	5 – 15 %	

4. First-aid Measures	
-----------------------	--

Take off all contaminated	clothing immediately.	
In case of ingestion: Seek medical advice immediately.		
In case of skin contact:	Wipe with paper towel and immediately clean with water and	
In case of eyes contact:	soap.	

5. Fire Fighting Measures	
Suitable extinguishing media:	All standard fire-fighting media.
Unsuitable extinguishing media:	Unknown
Hazardous decomposition:	Carbon dioxide, carbon monoxide, silicone dioxide and
COLUTION	acetic acid.
JULUHUN	

6. Accidental release measures

Methods for cleaning up:	Take

Take up mechanically.

7. Handling and Storage	
Handling:	Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep container tightly closed and dry.
Cautions:	Extreme heavy in drum form if product packed in 200L drum.



REV : 02 DATE : 15th Aug 2018

SAFETY DATA SHEET

SILOCK®

625°F BLACK RTV SILICONE

8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Local exhaust: General ventilation: Hand protection: Eye protection: Flammability:

Not indicated. recommended suitable protective gloves. Safety/ protective glasses. Combustible

9. Physical and Chemical Properties

Form:	
Specific gravity:	
Colour:	
Viscosity:	
Odour:	
Volatile % (25°C):	
Solubility in water:	
Boiling point:	
Flash point:	
Ignition temperature:	

Paste 1.03 ± 0.03 Black Not indicated Acetic Acid < 10% Insoluble Non known Non known Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability: Incompatibility (material to be avoid): Conditions to be avoid: Dangerous reactions: Dangerous products of decomposition:

Stable Water High temperature None known Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde

11. Toxicological Information	
Acute toxicity: Primary irritant effect,	Not determined
On the skin: On the eye: Sensitization: Additional Toxicological information:	Irritant for skin and mucous membranes. Irritant effect Sensitization possible by inhalation. When used and handled according to specification, the product does not have any harmful effects
	according to our experience and the information provided to us.



REV : 02 DATE : 15th Aug 2018

SAFETY DATA SHEET



625°F BLACK RTV SILICONE

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable. With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name:Silicone SealantHazard technical name:Not available.Hazard class:Not available.No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of SDS ***