

REV : 02  
DATE : 15<sup>th</sup> Aug 2018

## SAFETY DATA SHEET

### SL-930 AWNING & ROOFING SEALANT

#### 1. Product & Company Identification

##### 1.1 Product Details

Product name: SL-930 Awning & Roofing Sealant  
Physical form: Paste  
Odour: Mild Vegetable Oils odour  
CAS No.: Mixture

##### 1.2 Company Details

Manufacturer: Silock Technical Inc.  
Address: Nevada 89102 USA

#### 2. Hazards Identification

##### Hazard Pictogram



Signal Word: Warning

##### Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2
Flammable liquids	Category 3

##### Hazard Statement

H226 - Flammable liquid and vapour.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.

##### Precautionary Statement – Prevention

P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P233 - Keep container tightly closed.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P264 - Wash thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

REV : 02  
DATE : 15<sup>th</sup> Aug 2018

## SAFETY DATA SHEET



### SL-930 AWNING & ROOFING SEALANT

#### Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice/attention.  
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P370 + P378 - In case of fire: Use dry chemical powder for extinction.

#### Precautionary Statement – Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

#### Precautionary Statement – Disposal

P501 - Dispose of contents/container in accordance with regulations made under the control of Pollution & Environmental Protection Acts.

### 3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Mineral Spirits	64742-48-9	1 – 10 %
Cobalt Dryer	-	< 5 %
Ethylene glycol	107-21-1	< 10 %
Titanium dioxide	13463-67-7	< 5 %

### 4. First-aid Measures

Take off all contaminated clothing immediately.  
In case of ingestion: Seek medical advice immediately.  
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.  
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

### 5. Fire Fighting Measures

Suitable extinguishing media: Water, foam, CO2, dry power and all standard fire-fighting media.  
Unsuitable extinguishing media: Unknown  
Hazardous decomposition: Not specified.

REV : 02  
 DATE : 15<sup>th</sup> Aug 2018

## SAFETY DATA SHEET



### SL-930 AWNING & ROOFING SEALANT

#### 6. Accidental release measures

Methods for cleaning up: Take up mechanically.

#### 7. Handling and Storage

Handling:	Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep container tightly closed and dry.
Cautions:	Extreme heavy in drum form if product packed in 200L drum.

#### 8. Exposure control / Personal protection

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/ protective glasses.
Flammability:	Flammable

#### 9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.60 ± 0.03
Colour:	Grey, White, Black
Odour:	Oleo-resinous
Volatile, % volume (25°C):	< 10%
Solubility in water:	Not soluble
Boiling point:	Non known
Flash point:	Non known
Ignition temperature:	Non known

Note: the above information is not intended for use in preparing specification.

#### 10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known
Conditions to be avoid:	None known
Dangerous reactions:	None known.
Dangerous products of decomposition:	No dangerous decomposition products known.

REV : 02  
DATE : 15<sup>th</sup> Aug 2018**SAFETY DATA SHEET****SL-930 AWNING & ROOFING SEALANT****11. Toxicological Information**

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

**12. Ecological Information**

Complete information not yet available.

**13. Disposal considerations**

Please consult with the operator of the waste disposal facility for any further information.  
With respect to local regulation, dispose of to suitable incineration plant.

**14. Transport Information**

Proper shipping name:	Oil Based Awning Caulks
Hazard technical name:	Not available.
Hazard class:	Not available.
No dangerous goods under the transport regulation.	

**15. Regulatory Information**

Labeling (EC): This product is not subject to the labeling requirements.

**16. Other Information**

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.