



DATE: 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

1. Product & Company Identification

Product Details

Product name: SL-332 Multi-Purpose Epoxy Putty (Part A - Resin)

Physical form: Putty

Odour: Characteristic Odour

CAS No.: Mixture Flammability: Combustible.

Company Details:

Manufacturer: Silock Technical Inc.
Address: Nevada 89102 USA

2. Hazards Identification

Hazard Pictogram



Signal word: Warning

Classification

Eye irritation Category 2
Corrosion / irritation Category 2
Hazardous to the aquatic environment - chronic Category 2

hazard

Skin sensitization Category 1

Hazard statement

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statement - General

P102 - Keep out of the reach of children.

<u>Precautionary statement - Prevention</u>

P280 - Wear protective gloves and eye / face protection.





DATE: 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

<u>Precautionary statement - Response</u>

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice / attention.

Precautionary statement - Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
Chemical Name	CAS No.	<u>WT%</u>
Epoxy Resin	25068-38-6	45%
Calcium carbonate	1317-65-3	55%

4. First-aid Measures		
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.	
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.	
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.	
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.	
Skin contact:	Wash with plenty of soap and water.	

5. Fire Fighting Measures	
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO ₂)
Special protective actions for fire-fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO ₂)





DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency: Take people to safety place.

For workers, emergency If exposed to vapors/dust/ aerosols/gases, wear breathing

responders: apparatus.

Environmental precautions: Prevent spillage into drains, surface water and

groundwater.

Clean-up methods: Covering of drains. Wipe off with absorbent material (eg.

Textiles, non-woven fabric). Transfer leaked substances into suitable containers for disposal. Ventilate affected

area.

7. Handling and Storage

Handling: After use, wash your hands. Do not eat, drink or smoke in

the workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store chemicals in containers that are usually used to store food

or drinks. Avoid breathing vapor and mist.

Storage: Keep in cool, well-ventilated area away from heat, sparks and open flame. Use only compatible container

and keep container tightly closed/sealed until ready for

use.

8. Exposure control / Personal protection

Occupational exposure limits: No specific date.

Engineering controls: No special ventilation requirements. Good general

ventilation should be sufficient to control worker exposure

to airborne contaminants.

Environmental exposure control: Emissions from ventilation or work process equipment

should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary

to reduce emissions to acceptable levels.

Respiratory protection: Use a properly fitted, particular filter respiratory complying

with an approved standard if a risk assessment indicates

this is necessary.

Skin protection: Chemical resistance, impervious gloves complying with

an approved standard should be worn at all times when handling chemical products if a risk assessment indicates





DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

this is necessary.

Eye/face protection: Safety eyewear complying with an approved standard

> should be used when a risk assessment indicated this is necessary to avoid exposure to liquid splashes, mists,

gases, or dusts.

9. Physical and Chemical Properties

Physical state: **Putty** Viscosity: Unresolved Color: White Flash point: Unresolved Odor: Characteristic odor Specific gravity: 1.90±0.05 at

25°C

Unresolved Not relevant pH: Flammability: No

Melting/Freezing Unresolved **Explosive** properties:

point:

Boiling point/range: Unresolved Oxidizing No

properties:

10. Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this

product or its ingredients.

Chemical Stability: The product is stable.

Hazardous Reaction: Under normal conditions of storage and uses, hazardous

reactions will not occur.

Hazardous combustion: See section 5. Incompatibility: No specific data.

Keep away from heat, hot surfaces, sparks, open flames Conditions to avoid:

and other ignition sources. No smoking. Strong acids,

strong oxidizing agents and strong bases.

11. Toxicological Information

Information on toxicological

effects:

Test data are not available for the complete mixture. Method for classification of a mixture based on the

components of the mixture (additivity formula).

GHS Classification (1272.2008 / EC, CLP)

Acute toxicity: Not classified as acutely toxic.

Route of exposure	Property (Monitored)	Value	Test animal
Oral	LD50	>2.000 mg/kg	Rat
Dermal	LD50	>2.000 mg/kg	Rat

CAS: 25068-38-6

Skin corrosion / irritation:

Serious eye damage / eye

irritation:

Irritates the skin. It causes serious eye irritation.

Page 4 of 12



DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

May cause allergic skin reaction. Respiratory / skin sensitization:

Summary of the CMR properties: It not classified as mutagens for germ cells, carcinogenic

or reproductive toxicant.

Toxicity for specific target organ

toxicity (STOT):

It not classified as toxic to specific target organs.

Aspiration hazard: It not classified as aspiration hazard.

12. Ecological Information

Toxicity: Toxic to aquatic organisms.

Aquatic toxicity (acute)

Property (Monitored) Value Test animal **Exposure** time LC50 0.209 mg/l 96 hours Fish

CAS: 25068-38-6

Aquatic toxicity (chronic): Toxic to aquatic life with long lasting effects.

Persistence and degradability: BOD5 / COD. Insignificant.

bioaccumulation potential: Data not available. Mobility in soil: Data not available.

The results of The results of the

Data not available. assessment vPvB and vPvB:

Data not available. Other adverse effects:

13. Disposal Considerations

Information provided is for unused product only

Recommended

It is a hazardous waste, only containers that are approved (eg. By method of disposal: ADR) can be used. Completely emptied containers can be recycled.

> Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local

regulations.

14. Transport Information

U.S Department of Transportation Ground (49 CFR):

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division:

Identification number: **UN 3082** Packaging group: Ш **Exceptions:** None

Marine pollutant: Hazardous to the aquatic environment.

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division:

Identification number: **UN 3082**

Packaging group: Ш





DATE : 20th June 2023

SAFETY DATA SHEET

SILOCK®

SL-332 MULTI-PURPOSE EPOXY PUTTY

Exceptions: None

Water Transportation (IMO/IMDG):

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division:

Identification number: UN 3082

Packaging group:

Marine pollutant: Hazardous to the aquatic environment.

15. Regulatory Information

Chemical Safety Assessment: Chemical safety assessments for substances in this mixture

Information not available

were not carried out

Regulations concerning safety,

health and environmental regulations / legislation specific for the substance or

mixture:

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

** End of SDS ***





DATE: 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

1. Product & Company Identification

Product Detail

Product name: SL-332 Multi-Purpose Epoxy Putty (Part B - Hardener)

Physical form: Putty

Odour: Characteristic Odour

CAS No.: Mixture Flammability: Combustible.

Company Details:

Manufacturer: Silock Technical Inc. Address: Nevada 89102 USA

2. Hazards Identification

Hazard Pictogram



Signal word: Warning

Classification

<u> </u>	
Series eye damage / Eye irritation	Category 2
Skin Corrosion / Irritation	Category 2
Skin sensitization	Category 1

Hazard statement

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause allergic skin reaction.

<u>Precautionary statement - General</u>

P102 - Keep out of the reach of children.

Precautionary statement - Prevention

P280 - Wear protective gloves and eye / face protection.

<u>Precautionary statement - Response</u>

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.





DATE: 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice / attention.

Precautionary statement - Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
<u>Chemical Name</u>	CAS No.	<u>WT</u> <u>%</u>
Epoxy Hardener	68410-23-1	45 %
Calcium carbonate	1317-65-3	55 %

4. First-aid Measures		
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.	
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.	
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.	
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.	
Skin contact:	Wash with plenty of soap and water.	

5. Fire Fighting Measures	
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO_2)
Special protective actions for fire-fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO ₂)





DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

6. Accidental release measures

<u>Personal precautions</u>, <u>protective equipment and emergency procedures</u>

Take people to safety place. For non-emergency:

For workers, If exposed to vapors/dust/ aerosols/gases, wear breathing apparatus.

emergency responders:

Environmental precautions:

Clean-up methods:

Prevent spillage into drains, surface water and groundwater.

Covering of drains. Wipe off with absorbent material (eg. Textiles, nonwoven fabric). Transfer leaked substances into suitable containers for

disposal. Ventilate affected area.

7. Handling and Storage

Handling: After use, wash your hands. Do not eat, drink or smoke in the

> workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store chemicals in containers that are usually used to store food or drinks. Avoid breathing vapor and

Storage: Keep in cool, well-ventilated area away from heat, sparks and

open flame. Use only compatible container and keep container

tightly closed/sealed until ready for use.

8. Exposure control / Personal protection

Occupational exposure

limits:

No specific date.

Engineering controls:

No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

Environmental exposure

control:

Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of

environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

Respiratory protection: Use a properly fitted, particular filter respiratory complying with

an approved standard if a risk assessment indicates this is

necessary.

Skin protection: Chemical resistance, impervious gloves complying with an

> approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye/face protection: Safety eyewear complying with an approved standard should

be used when a risk assessment indicated this is necessary to





DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

avoid exposure to liquid splashes, mists, gases, or dusts.

9. Physical and Chemical Properties

Physical state: Putty Viscosity: Unresolved

Color: Reddish pink Flash point: Unresolved Odor: Characteristic odor Specific gravity: 1.90±0.05 at

25°C

Not relevant Unresolved Flammability: :Ha

Melting/Freezing Unresolved **Explosive properties:** No

point:

Boiling Unresolved Oxidizing properties: No

point/range:

10. Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this

product or its ingredients

Chemical Stability: The product is stable.

Under normal conditions of storage and uses, hazardous **Hazardous Reaction:**

reactions will not occur.

Hazardous combustion products:

See section 5. Incompatibility: No specific data. Conditions to avoid: No specific data.

11. Toxicological Information

Information on toxicological Test data are not available for the complete mixture.

Method for classification of a mixture based on the

components of the mixture (additivity formula).

GHS Classification (1272.2008 / EC, CLP)

Acute toxicity: Not classified as acutely toxic.

Skin corrosion / irritation: Irritates the skin.

Serious eye damage / eye irritation: It causes serious eye irritation. Respiratory / skin sensitization: May cause allergic skin reaction.

Summary of the CMR properties: It not classified as mutagens for germ cells, carcinogenic

or reproductive toxicant.

Toxicity for specific target organ

toxicity (STOT):

effects:

It not classified as toxic to specific target organs.

Aspiration hazard: It not classified as aspiration hazard.



DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

12. Ecological Information

Toxicity:

Persistence and degradability:
bioaccumulation potential:
Mobility in soil:

The results of The results of the

No specific data.
No specific data.
No specific data.
No specific data.

The results of The results of the assessment vPvB and vPvB:

Other adverse effects:

No known significant effects or critical hazards.

13. Disposal Considerations

Information provided is for unused product only

Recommended It is a hazardous waste, only containers that are approved (eg. By method of disposal: ADR) can be used. Completely emptied containers can be recycled.

Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local

regulations.

14. Transport Information

U.S Department of Transportation Ground (49 CFR):

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division:

Identification number:

Packaging group:

Exceptions:

Marine pollutant:

None

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division: 8

Identification number: UN 1760
Packaging group: III
Exceptions: None

Water Transportation (IMO/IMDG):

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division: 8

Identification number:UN 1760Packaging group:IIIMarine pollutant:None.

15. Regulatory Information





DATE : 20th June 2023

SAFETY DATA SHEET



SL-332 MULTI-PURPOSE EPOXY PUTTY

Chemical Safety Assessment:

Chemical safety assessments for substances in this mixture were not carried out

Regulations concerning safety, health and environmental regulations / legislation specific for the substance or mixture: Information not available

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

** End of SDS ***

