



DATE : 10th May 2019

# **SAFETY DATA SHEET**



### SL-332 MULTI-PURPOSE EPOXY PUTTY

# 1. Product & Company Identification

#### **Product Details**

Product name: SL-332 Multi-Purpose Epoxy Putty (Part A - Resin)

Physical form: Putty

Odour: Characteristic Odour

CAS No.: Mixture Flammability: Combustible.

Company Details:

Manufacturer: Silock Technical Inc. Address: Nevada 89102 USA

### 2. Hazards Identification

#### **Hazard Pictogram**





Signal word: Warning

#### Classification

Eye irritation Category 2
Corrosion / irritation Category 2
Hazardous to the aquatic environment - chronic Category 2

hazard

Skin sensitization Category 1

#### Hazard statement

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause allergic skin reaction.

H411 - Toxic to aquatic life with long lasting effects.

#### Precautionary statement - General

P102 - Keep out of the reach of children.

#### <u>Precautionary statement - Prevention</u>

P280 - Wear protective gloves and eye / face protection.





DATE : 10th May 2019

# **SAFETY DATA SHEET**



### SL-332 MULTI-PURPOSE EPOXY PUTTY

#### Precautionary statement - Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice / attention.

#### Precautionary statement - Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
<u>Chemical Name</u>	CAS No.	<u>WT%</u>
Epoxy Resin	25068-38-6	45%
Calcium carbonate	1317-65-3	55%

4. First-aid Measures		
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.	
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.	
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.	
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.	
Skin contact:	Wash with plenty of soap and water.	

5. Fire Fighting Measures	
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO <sub>2</sub> )
Special protective actions for fire-fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO <sub>2</sub> )





DATE : 10th May 2019

### SAFETY DATA SHEET



#### SL-332 MULTI-PURPOSE EPOXY PUTTY

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency: Take people to safety place.

responders: apparatus.

Environmental precautions: Prevent spillage into drains, surface water and

groundwater.

Clean-up methods: Covering of drains. Wipe off with absorbent material (eg.

Textiles, non-woven fabric). Transfer leaked substances into suitable containers for disposal. Ventilate affected

area.

7. Handling and Storage

Handling: After use, wash your hands. Do not eat, drink or smoke in

the workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store chemicals in containers that are usually used to store food

or drinks. Avoid breathing vapor and mist.

Storage: Keep in cool, well-ventilated area away from heat, sparks and open flame. Use only compatible container

and keep container tightly closed/sealed until ready for

use.

# 8. Exposure control / Personal protection

Occupational exposure limits: No specific date.

Engineering controls: No special ventilation requirements. Good general

ventilation should be sufficient to control worker exposure

to airborne contaminants.

Environmental exposure control: Emissions from ventilation or work process equipment

should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary

to reduce emissions to acceptable levels.

Respiratory protection: Use a properly fitted, particular filter respiratory complying

with an approved standard if a risk assessment indicates

this is necessary.

Skin protection: Chemical resistance, impervious gloves complying with

an approved standard should be worn at all times when handling chemical products if a risk assessment indicates





REV : 01

DATE : 10th May 2019

### SAFETY DATA SHEET



#### SL-332 MULTI-PURPOSE EPOXY PUTTY

this is necessary.

Eye/face protection: Safety eyewear complying with an approved standard

should be used when a risk assessment indicated this is necessary to avoid exposure to liquid splashes, mists,

gases, or dusts.

9. Physical and Chemical Properties

Physical state: **Puttv** Viscosity: Unresolved Color: White Flash point: Unresolved Odor: Characteristic odor Specific gravity: 1.90±0.05 at

25°C

Unresolved pH: Flammability: Not relevant

Melting/Freezing Unresolved **Explosive** No

point:

Boiling point/range: Unresolved Oxidizing No

properties:

properties:

10. Stability and Reactivity

No specific test data related to reactivity available for this Reactivity:

product or its ingredients.

**Chemical Stability:** The product is stable.

**Hazardous Reaction:** Under normal conditions of storage and uses, hazardous

reactions will not occur.

Hazardous combustion: See section 5. Incompatibility: No specific data.

Keep away from heat, hot surfaces, sparks, open flames Conditions to avoid:

and other ignition sources. No smoking. Strong acids,

strong oxidizing agents and strong bases.

Toxicological Information

Information on toxicological Test data are not available for the complete mixture. effects:

Method for classification of a mixture based on the

components of the mixture (additivity formula).

GHS Classification (1272.2008 / EC, CLP)

Acute toxicity: Not classified as acutely toxic.

Test animal Route of exposure Property (Monitored) Value Oral LD50 >2.000 mg/kg Rat LD50 >2.000 mg/kg Rat Dermal

CAS: 25068-38-6

Skin corrosion / irritation: Irritates the skin.

Serious eye damage / eye It causes serious eye irritation.

irritation:





DATE : 10th May 2019

### SAFETY DATA SHEET



### SL-332 MULTI-PURPOSE EPOXY PUTTY

Respiratory / skin sensitization: May cause allergic skin reaction.

Summary of the CMR properties: It not classified as mutagens for germ cells, carcinogenic

or reproductive toxicant.

Toxicity for specific target organ

toxicity (STOT):

It not classified as toxic to specific target organs.

Aspiration hazard: It not classified as aspiration hazard.

12. Ecological Information

Toxicity: Toxic to aquatic organisms.

Aquatic toxicity (acute)

Property (Monitored)

Value

Test animal

Exposure time

LC50

0.209 mg/l

Fish

96 hours

CAS: 25068-38-6

Aquatic toxicity (chronic): Toxic to aquatic life with long lasting effects.

Persistence and degradability: BOD5 / COD. Insignificant.

bioaccumulation potential: Data not available.

Mobility in soil:

The results of the Data not available.

Data not available.

assessment vPvB and vPvB:

Other adverse effects: Data not available.

### 13. Disposal Considerations

Information provided is for unused product only

DDOFFCCI

Recommended It is a hazardous waste, only containers that are approved (eg. By method of disposal: ADR) can be used. Completely emptied containers can be recycled.

Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local

regulations.

#### 14. Transport Information

**U.S Department of Transportation Ground (49 CFR):** 

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division:

Identification number:UN 3082Packaging group:IIIExceptions:None

Marine pollutant: Hazardous to the aquatic environment.

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division: 9

Identification number: UN 3082 Packaging group: III





DATE : 10th May 2019

### SAFETY DATA SHEET

SILOCK® PROFESSIONAL

SL-332 MULTI-PURPOSE EPOXY PUTTY

Exceptions: None

Water Transportation (IMO/IMDG):

Proper Shipping Name: Environmentally Hazardous Substance, Liquid, N.O.S

Hazard class or division: 9

Identification number: UN 3082

Packaging group: III

Marine pollutant: Hazardous to the aquatic environment.

15. Regulatory Information

Chemical Safety Assessment: Chemical safety assessments for substances in this mixture

were not carried out Information not available

Regulations concerning safety, health and environmental

regulations / legislation specific for the substance or

mixture:

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

End of SDS \*\*\*





DATE : 10th May 2019

# **SAFETY DATA SHEET**



### SL-332 MULTI-PURPOSE EPOXY PUTTY

### 1. Product & Company Identification

**Product Detail** 

Product name: SL-332 Multi-Purpose Epoxy Putty (Part B - Hardener)

Physical form: Putty

Odour: Characteristic Odour

CAS No.: Mixture Flammability: Combustible.

Company Details:

Manufacturer: Silock Technical Inc. Address: Nevada 89102 USA

#### 2. Hazards Identification

#### **Hazard Pictogram**



Signal word: Warning

#### Classification

<u> </u>	
Series eye damage / Eye irritation	Category 2
Skin Corrosion / Irritation	Category 2
Skin sensitization	Category 1

#### **Hazard statement**

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause allergic skin reaction.

#### Precautionary statement - General

P102 - Keep out of the reach of children.

#### Precautionary statement - Prevention

P280 - Wear protective gloves and eye / face protection.

#### <u>Precautionary statement - Response</u>

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.





DATE : 10th May 2019

# SAFETY DATA SHEET



### SL-332 MULTI-PURPOSE EPOXY PUTTY

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice / attention.

Precautionary statement - Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
<u>Chemical Name</u>	CAS No.	<u>WT</u>
		<u>%</u>
Epoxy Hardener	68410-23-1	45
Calcium carbonate	1317-65-3	% 55
		%

4. First-aid Measures	
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.
Skin contact:	Wash with plenty of soap and water.

5. Fire Fighting Measures		
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO <sub>2</sub> )	
Special protective actions for fire-fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Unusual fire or explosion hazards:	None	
Hazardous combustion products:	Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO <sub>2</sub> )	





DATE : 10th May 2019

### SAFETY DATA SHEET



#### SL-332 MULTI-PURPOSE EPOXY PUTTY

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency: Take people to safety place.

For workers, If exposed to vapors/dust/ aerosols/gases, wear breathing apparatus.

emergency responders:

Environmental Prevent spillage into drains, surface water and groundwater.

precautions:

Clean-up methods: Covering of drains. Wipe off with absorbent material (eg. Textiles, non-

woven fabric). Transfer leaked substances into suitable containers for

disposal. Ventilate affected area.

7. Handling and Storage

Handling: After use, wash your hands. Do not eat, drink or smoke in the

workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store chemicals in containers that are usually used to store food or drinks. Avoid breathing vapor and

mist.

Storage: Keep in cool, well-ventilated area away from heat, sparks and

open flame. Use only compatible container and keep container

tightly closed/sealed until ready for use.

8. Exposure control / Personal protection

Occupational exposure

limits:

No specific date.

**Engineering controls:** 

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne

contaminants.

**Environmental exposure** 

control:

Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of

checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

ieveis.

Respiratory protection: Use a properly fitted, particular filter respiratory complying with

an approved standard if a risk assessment indicates this is

necessary.

Skin protection: Chemical resistance, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Eye/face protection: Safety eyewear complying with an approved standard should

be used when a risk assessment indicated this is necessary to





REV : 01

DATE : 10th May 2019

### SAFETY DATA SHEET



### SL-332 MULTI-PURPOSE EPOXY PUTTY

avoid exposure to liquid splashes, mists, gases, or dusts.

9. Physical and Chemical Properties

Physical state: Viscosity: Unresolved Putty Color: Reddish pink Flash point: Unresolved

Odor: Characteristic odor Specific gravity: 1.90±0.05 at

25°C

pH: Unresolved Flammability: Not relevant

Melting/Freezing Unresolved **Explosive properties:** No

point:

effects:

**Boiling** Unresolved Oxidizing properties: No

point/range:

10. Stability and Reactivity

Reactivity: No specific test data related to reactivity available for this

product or its ingredients

The product is stable. **Chemical Stability:** 

**Hazardous Reaction:** Under normal conditions of storage and uses, hazardous

reactions will not occur.

Hazardous combustion products:

See section 5. No specific data. Incompatibility: Conditions to avoid: No specific data.

11. Toxicological Information

Information on toxicological Test data are not available for the complete mixture.

Method for classification of a mixture based on the

components of the mixture (additivity formula).

GHS Classification (1272.2008 / EC, CLP)

Acute toxicity: Not classified as acutely toxic.

Skin corrosion / irritation: Irritates the skin.

Serious eye damage / eye irritation: It causes serious eye irritation. Respiratory / skin sensitization: May cause allergic skin reaction.

Summary of the CMR properties: It not classified as mutagens for germ cells, carcinogenic

or reproductive toxicant.

Toxicity for specific target organ

toxicity (STOT):

It not classified as toxic to specific target organs.

Aspiration hazard: It not classified as aspiration hazard.





DATE : 10th May 2019

### SAFETY DATA SHEET



#### SL-332 MULTI-PURPOSE EPOXY PUTTY

12. Ecological Information

Toxicity:

Persistence and degradability:
bioaccumulation potential:

Mobility in soil:

The results of The results of the

No specific data.

No specific data.

No specific data.

No specific data.

The results of The results of the assessment vPvB and vPvB:

Other adverse effects: No known significant effects or critical hazards.

### 13. Disposal Considerations

Information provided is for unused product only

Recommended It is a hazardous waste, only containers that are approved (eg. By method of disposal: ADR) can be used. Completely emptied containers can be recycled.

Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local

regulations.

### 14. Transport Information

**U.S Department of Transportation Ground (49 CFR):** 

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division: 8
Identification number: UN 1760
Packaging group: III
Exceptions: None

Marine pollutant: None.

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division: 8

Identification number:UN 1760Packaging group:IIIExceptions:None

Water Transportation (IMO/IMDG):

Proper Shipping Name: Liquid, Corrosive N.O.S

Hazard class or division: 8

Identification number: UN 1760
Packaging group: III
Marine pollutant: None.





DATE : 10th May 2019

# **SAFETY DATA SHEET**



### SL-332 MULTI-PURPOSE EPOXY PUTTY

### 15. Regulatory Information

Chemical Safety Assessment: Chemical safety assessments for substances in this

mixture were not carried out Information not available

Regulations concerning safety, health and environmental regulations / legislation specific for the substance or mixture:

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

