



: 03 REV

DATE : 20th June 2023

## **SAFETY DATA SHEET**



## SILOCK® SL-712 WEATHER LOCK NEUTRAL SILICONE **SEALANT (LM)**

## 1. Product & Company Identification

1.1 Product Details

Product name: SL-712 Weather Lock Neutral Silicone Sealant (LM)

Physical form: **Paste** 

Odour: **Low Oxime Odour** 

CAS No.: **Mixture** 

1.2 Company Details

Manufacturer: Silock Technical Inc. Address: Nevada 89102 USA

### 2. Hazards Identification

## Hazard Pictogram



### **Signal Word: Warning**

# <u>Classification</u>

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2
May cause respiratory irritation	Category 3

### **Hazard Statement**

H315 - Causes skin irritation.

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

#### Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

### <u>Precautionary Statement - Response</u>





REV : 03

DATE : 20th June 2023

## SAFETY DATA SHEET



## SILOCK® SL-712 WEATHER LOCK NEUTRAL SILICONE SEALANT (LM)

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

<u>Precautionary Statement - Storage</u>

No precautionary statement

Precautionary Statement - Disposal

No precautionary statement

### 3. Composition / Hazardous Components

Chemical Name	CAS No.	<u>WT%</u>
Methyl Tri (Methylethylketoxime)	22984-54-9	1 – 5 %
Silane		
Vinyl Tri (Methylethylketoxime) Silane	2224-33-1	1 – 5 %
Treated Fume Silica	68583-49-3	5 – 15 %

## 4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and

In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

### 5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media: Unknown

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and

nitrogen oxides and formaldehyde.

#### 6. Accidental release measures

Methods for cleaning up: Take up mechanically.

## 7. Handling and Storage





REV : 03

DATE : 20th June 2023

## SAFETY DATA SHEET



## SILOCK® SL-712 WEATHER LOCK NEUTRAL SILICONE SEALANT (LM)

Handling: Avoid contact with eyes and skin. Ensure good ventilation

during processing. Wear safety shoes.

Protection against fire/

explosion:

General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L

drum.

### 8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended General ventilation: Recommended

Hand protection: Suitable protective gloves. Eye protection: Safety/ protective glasses.

Combustible Flammability:

Note: Until more data is known, exposure levels should be maintained as low as achievable.

### 9. Physical and Chemical Properties

Form: Paste Specific gravity: 1.40 ± 0.05 Colour: Matte Colour Not indicated. Viscosity: Oxime Odour Odour:

Volatile, % volume (25°C): < 5%

Boiling point: Not Applicable. Not Applicable. Flash point: Ignition temperature: Not Applicable. Solubility in water: Insoluble Vapour pressure: Not Applicable.

Solubility in organic solvent: Toluene.

Note: the above information is not intended for use in preparing specification.

## 10. Stability and Reactivity

Chemical stability: **Stable** 

Incompatibility (material to be avoid): None known. Conditions to be avoid: None known. Dangerous reactions: None known.

Dangerous products of decomposition: Ketoxime during curing.





REV : 03

DATE : 20th June 2023

## SAFETY DATA SHEET



## SILOCK<sup>®</sup> SL-712 WEATHER LOCK NEUTRAL SILICONE SEALANT (LM)

In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.

## 11. Toxicological Information

Acute toxicity: Not determined

Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Sensitization: Sensitization possible by inhalation.

Additional Toxicological information: Until more data is known, exposure levels should be

maintained as low as achievable.

### 12. Ecological Information

Complete information not yet available.

#### 13. Disposal considerations

For cured sealant landfill may be suitable.

With respect to local regulation, dispose to suitable incineration plant.

### 14. Transport Information

Proper shipping name: Silicone Sealant Hazard technical name: Not available. Hazard class: Not available. No dangerous goods under the transport regulation.

## 15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.