

MATERIAL SAFETY DATA SHEET

SL-930 MULTIPURPOSE AWNING CAULK JOINT SEALING & WATERPROOFING COMPOUND (LOW VOC)



1. Product & Company Identification

1.1 Product Detail

Product name: Multipurpose Awning Caulk Joint Sealing & Waterproofing Compound (Low VOC)
Physical form: Paste
Odour: Mild Vegetable Oils odour
CAS No.: Mixture

1.2 Company Details:

Manufacturer: Silock Technical Inc.
Address: Nevada 89102 USA

2. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Mineral Spirits	64742-48-9	1 – 10 %
Cobalt Dryer	-	< 5 %
Ethylene glycol	107-21-1	< 10 %
Titanium dioxide	13463-67-7	< 5 %

3. Hazards Identification

Ingestion: Irritation of the mouth, throat and stomach.
Skin contact: Uncured product contact will irritate lips, gums and tongue.
Uncured product contact may irritate the skin.
Inhalation: May cause mild respiratory irritation.
Eye contact: Uncured product contact irritates eyes.

4. First-aid Measures

Take off all contaminated clothing immediately.
In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: Water, foam, CO2, dry power and all standard fire-fighting media.
Unsuitable extinguishing media: Unknown
Hazardous decomposition: Not specified.

MATERIAL SAFETY DATA SHEET

SL-930 MULTIPURPOSE AWNING CAULK JOINT SEALING & WATERPROOFING COMPOUND (LOW VOC)



6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion: General rules of fire prevention should be observed.
Storage: Keep container tightly closed and dry.
Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Not indicated.
Local exhaust: Recommended
General ventilation: Recommended
Hand protection: Suitable protective gloves.
Eye protection: Safety/ protective glasses.
Flammability: Flammable

9. Physical and Chemical Properties

Form: Paste
Specific gravity: 1.60 ± 0.03
Colour: Grey, White, Black
Odour: Oleo-resinous
Volatile, % volume (25°C): < 10%
Solubility in water: Not soluble
Boiling point: Non known
Flash point: Non known
Ignition temperature: Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability: Stable
Incompatibility (material to be avoid): None known
Conditions to be avoid: None known
Dangerous reactions: None known.
Dangerous products of decomposition: No dangerous decomposition products known.

MATERIAL SAFETY DATA SHEET



**SL-930 MULTIPURPOSE AWNING
CAULK JOINT SEALING & WATERPROOFING
COMPOUND (LOW VOC)**



11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

Please consult with the operator of the waste disposal facility for any further information.
With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name:	Oil Based Awning Caulks
Hazard technical name:	Not available.
Hazard class:	Not available.
No dangerous goods under the transport regulation.	

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***