

## SAFETY DATA SHEET

SILOCK®

# **4 MINUTES STEEL EPOXY**

#### 1. Product & Company Identification


#### **Product Details**

Product name:	4 Minutes Steel Epoxy (Part A - Resin)
Physical form:	Paste Form
Odour:	Sulfur- Like
CAS No.:	Mixture
Flammability:	Combustible.

#### **Company Details**

Manufacturer:	Silock Technical Inc.
Address:	Nevada 89102 USA

#### 2. Hazards Identification



Signal word: Warning

CI	assifi	cati	on

Eye irritation	Category 2
Corrosion / irritation	Category 2
Hazardous to the aquatic environment - chronic hazard	Category 2
Skin sensitization	Category 1

#### Hazard statement

H319 - Causes serious eye irritation.

- H315 Causes skin irritation.
- H317 May cause allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statement - General

P102 - Keep out of the reach of children.

<u>Precautionary statement - Prevention</u> P280 - Wear protective gloves and eye / face protection.

Precautionary statement - Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.



## SAFETY DATA SHEET



## **4 MINUTES STEEL EPOXY**

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice / attention.

#### Precautionary statement - Disposal

\_ \_ \_ \_ \_ \_

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
Chemical Name	CAS No.	<u>WT%</u>
Epoxy Resin	25068-38-6	60%
Calcium Carbonate	1317-65-3	40%

4. First-aid Measures	
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.
Skin contact:	Wash with plenty of soap and water.

5. Fire Fighting Measures	
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO2)
Special protective actions for fire- fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Unusual fire or explosion hazards: Hazardous combustion products:	None Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

WEBSITE: WWW.SILOCK.COM.MY

SILOCK TECHNICAL INC.

## SAFETY DATA SHEET



SIL@CK

# **4 MINUTES STEEL EPOXY**

ADDRESS: NEVADA 89102 USA.

6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures		
For non-emergency:	Take people to safety place.	
For workers, emergency responders:	If exposed to vapors/dust/ aerosols/gases, wear breathing apparatus.	
Environmental precautions:	Prevent spillage into drains, surface water and groundwater.	
Clean-up methods:	Covering of drains. Wipe off with absorbent material (eg. Textiles, non-woven fabric). Transfer leaked substances into suitable containers for disposal. Ventilate affected area.	

7. Handling and Sta	prage
Handling:	After use, wash your hands. Do not eat, drink or smoke in the workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store
	chemicals in containers that are usually used to store food or drinks. Avoid breathing vapor and mist.
Storage:	Keep in cool, well-ventilated area away from heat, sparks and open flame. Use only compatible container and keep container tightly closed/sealed until ready for use.

DDOEE	DOLONIAL		
8. Exposure control / Person	8. Exposure control / Personal protection		
Occupational exposure limits:	No specific date.		
Engineering controls:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.		
Environmental exposure control:	Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Respiratory protection:	Use a properly fitted, particular filter respiratory complying with an approved standard if a risk assessment indicates this is necessary.		
Skin protection:	Chemical resistance, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		

WEBSITE: WWW.SILOCK.COM.MY

K TECHNICAL INC.

### **SAFETY DATA SHEET**



## **4 MINUTES STEEL EPOXY**

SILOC

ADDRESS: NEVADA 89102 USA.

Eye/face protection:

OI

Safety eyewear complying with an approved standard should be used when a risk assessment indicated this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts.

9. Physical and Chemical Properties			
Physical state:	Paste	Viscosity:	Unresolved
Color:	Black	Flash point:	Unresolved
Odor:	Characteristic odor	Specific gravity:	1.75±0.05 at 25°C
pH:	Unresolved	Flammability:	Not relevant
Melting/Freezing point:	Unresolved	Explosive properties:	No
Boiling point/range:	Unresolved	Oxidizing properties:	No

10. Stability and Reactivity	ły
Reactivity:	No specific test data related to reactivity available for this product or its ingredients.
Chemical Stability:	The product is stable.
Hazardous Reaction:	Under normal conditions of storage and uses, hazardous reactions will not occur.
Hazardous combustion:	See section 5.
Incompatibility:	No specific data.
Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames
DDOEE	and other ignition sources. No smoking. Strong acids,
FROFE	strong oxidizing agents and strong bases.

COLUTION				
11. Toxicological Information				
effects: fo		Test data are not available for the complete mixture. Method for classification of a mixture based on the components of the mixture (additivity formula). EC, CLP)		
Acute toxicity: Not classified as acutely toxic.			acutely toxic.	
Route of exposure	Property	(Monitored)	Value	Test animal
Oral	LD50		>2.000 mg/kg	Rat
Dermal	LD50		>2.000 mg/kg	Rat
CAS: 25068-38-6				
Skin corrosion / irritation: Serious eye damage / eye irritation:		Irritates the skin. It causes serious eye irritation.		
Respiratory / skin sensitization: Summary of the CMR properties:		•		erm cells, carcinogenic

WEBSITE: WWW.SILOCK.COM.MY

TECHNICAL

## SAFETY DATA SHEET



O

## **4 MINUTES STEEL EPOXY**

ADDRESS: NEVADA 89102 USA.

Toxicity for specific target organIt not classified as toxic to specific target organs.toxicity (STOT):It not classified as aspiration hazard.

12. Ecological Information				
Toxicity: Aquatic toxicity (acute)	Toxic to a	quatic organ	iisms.	
Property (Monitored)	Value		Test animal	Exposure time
LC50	0.209 m	ng/l	Fish	96 hours
		CAS: 250	)68-38-6	
Aquatic toxicity (chronic):Toxic to aquatic life with long lasting effects.Persistence and degradability:BOD5 / COD. Insignificant.bioaccumulation potential:Data not available.Mobility in soil:Data not available.The results of The results of the assessment vPvB and vPvB:Data not available.				
Other adverse effects: Data not available.				

#### 13. Disposal Considerations

Information provided is for unused product only

Recommended method of disposal:

It is a hazardous waste, only containers that are approved (eg. By ADR) can be used. Completely emptied containers can be recycled. Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local regulations.

14. Transport Information	
U.S Department of Transporta	tion Ground (49 CFR):
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S
Hazard class or division:	9
Identification number:	UN 3082
Packaging group:	III
Exceptions:	None
Marine pollutant:	Hazardous to the aquatic environment.
International Air Transportatio	n (ICAO/IATA):
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S
Hazard class or division:	9
Identification number:	UN 3082
Packaging group:	III
Exceptions:	None

WEBSITE: WWW.SILOCK.COM.MY

## SAFETY DATA SHEET

SILOCK

## **4 MINUTES STEEL EPOXY**

ADDRESS: NEVADA 89102 USA.

Water Transportation (IMO/IMDG):		
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S	
Hazard class or division:	9	
Identification number:	UN 3082	
Packaging group:	III	
Marine pollutant:	Hazardous to the aquatic environment.	

#### 15. Regulatory Information

O

Chemical Safety	Chamical safety assessments for substances in this mixture
-	Chemical safety assessments for substances in this mixture
Assessment:	were not carried out
Regulations concerning	Information not available
safety, health and	
environmental regulations /	
legislation specific for the	
substance or mixture:	

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.





## SAFETY DATA SHEET

SILOCK

# **4 MINUTES STEEL EPOXY**

#### 1. Product & Company Identification

#### **Product Detail**

Product name:	4 Minutes Steel Epoxy (Part B - Hardener)
Physical form:	Paste Form
Odour:	Sulfur- Like
CAS No.:	Mixture
Flammability:	Combustible.

#### **Company Details**

Manufacturer:	Silock Technical Inc.
Address:	Nevada 89102 USA

#### 2. Hazards Identification





Signal word: Warning

#### Classification

Series eye damage / Eye irritation	Category 2
Skin Corrosion / Irritation	Category 2
Skin sensitization	Category 1

#### Hazard statement

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H317 - May cause allergic skin reaction.

<u>Precautionary statement - General</u> P102 - Keep out of the reach of children.

Precautionary statement - Prevention

P280 - Wear protective gloves and eye / face protection.

Precautionary statement - Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P362 - Take off contaminated clothing and wash before reuse.

P333 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

WEBSITE: WWW.SILOCK.COM.MY

TECHNICAL II

SAFETY DATA SHEET

SILOCK"

**4 MINUTES STEEL EPOXY** 

ADDRESS: NEVADA 89102 USA.

contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice / attention.

Precautionary statement – Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Hazardous Components		
<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Epoxy Hardener	68410-23-1	60%
Calcium Carbonate	1317-65-3	40%

4. First-aid Mea	sures
General remarks:	Do not leave affected person unattended. Plot casualty from the danger area. Keep victim warm, calm and eclipsed. Remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. In case of unconsciousness place person in the recovery position. Never give anything by mouth.
Inhalation:	If the breathing is irregular or stopped, seek medical advice immediately and initiate first aid measures. In case of respiratory tract irritation, consult a physician. Provide fresh air.
Eye contact:	Remove contact lenses, if present and it can be removed easily. Continue rinsing. Hold eyelids stretched and rinse with plenty of clean, running water for 10 minutes.
Ingestion:	If swallowed, rinse your mouth with water (only if the person is conscious). Do not induce vomiting.
Skin contact:	Wash with plenty of soap and water.

5. Fire Fighting Measures	
Extinguishing media:	Water spray, alcohol-resistant foam, BC-powder, carbon dioxide (CO2)
Special protective actions for fire- fighters:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Unusual fire or explosion hazards: Hazardous combustion products:	None Nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency proceduresFor non-emergency:Take people to safety place.For workers, emergencyIf exposed to vapors/dust/ aerosols/gases, wear breathing

WEBSITE: WWW.SILOCK.COM.MY

OCK TECHNICAL INC.

## SAFETY DATA SHEET



SIL@CK

## **4 MINUTES STEEL EPOXY**

SIL

ADDRESS: NEVADA 89102 USA.

responders: Environmental precautions:	apparatus. Prevent spillage into drains, surface water and groundwater.
Clean-up methods:	Covering of drains. Wipe off with absorbent material (eg. Textiles, non-woven fabric). Transfer leaked substances into suitable containers for disposal. Ventilate affected area.

7. Handling and Storage	
Handling:	After use, wash your hands. Do not eat, drink or smoke in the workplace. Before entering eating areas remove contaminated clothing and protective equipment. No food or drink stored near the chemicals. Never store chemicals in containers that are usually used to store food or drinks. Avoid breathing vapor and mist.
Storage:	Keep in cool, well-ventilated area away from heat, sparks and open flame. Use only compatible container and keep container tightly closed/sealed until ready for use.

8. Exposure control / Personal protection		
Occupational exposure limits:	No specific date.	
Engineering controls:	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	
Environmental exposure control:	Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Respiratory protection:	Use a properly fitted, particular filter respiratory complying with an approved standard if a risk assessment indicates this is necessary.	
Skin protection:	Chemical resistance, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.	
Eye/face protection:	Safety eyewear complying with an approved standard should be used when a risk assessment indicated this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts.	

REV : 03 DATE : 20th June 2023

WEBSITE: WWW.SILOCK.COM.MY

K TECHNICAL INC.

## **SAFETY DATA SHEET**

S

Π ADDRESS: NEVADA 89102 USA.

SILOCK"

**O**CK

**4 MINUTES STEEL EPOXY** 

9. Physical and Chemical Properties			
Physical state:	Paste	Viscosity:	Unresolved
Color:	White	Flash point:	Unresolved
Odor:	Characteristic odor	Specific gravity:	1.55±0.05 at 25°C
pH:	Unresolved	Flammability:	Not relevant
Melting/Freezing point:	Unresolved	Explosive properties:	Νο
Boiling point/range:	Unresolved	Oxidizing properties:	Νο

No specific test data related to reactivity available for this product or its ingredients	
The product is stable.	
Under normal conditions of storage and uses, hazardous reactions will not occur.	
See section 5.	
No specific data.	
No specific data.	

11. Toxicological Information	
Information on toxicological Te	est data are not available for the complete mixture.
effects: N	Nethod for classification of a mixture based on the
DDOEEC	omponents of the mixture (additivity formula).
PRUFFS	SIUNAL
GHS Classification (1272.2008 / EC, C	CLP)
Acute toxicity:	Not classified as acutely toxic.
Skin corrosion / irritation:	Irritates the skin.
Serious eye damage / eye irritation:	It causes serious eye irritation.
Respiratory / skin sensitization:	May cause allergic skin reaction.
Summary of the CMR properties:	It not classified as mutagens for germ cells,
	carcinogenic or reproductive toxicant.
Toxicity for specific target organ	It not classified as toxic to specific target organs.
toxicity (STOT):	
Aspiration hazard:	It not classified as aspiration hazard.

#### 12. Ecological Information

Toxicity: N	lo specific data.
Persistence and degradat	oility: No specific data.
bioaccumulation potentia	II: No specific data.
Mobility in soil:	No specific data.
The results of The results of	the No specific data.
assessment vPvB and vPvI	B:

WEBSITE: WWW.SILOCK.COM.MY

## SAFETY DATA SHEET

SILOCK

# **4 MINUTES STEEL EPOXY**

ADDRESS: NEVADA 89102 USA.

Other adverse effects:

No known significant effects or critical hazards.

#### 13. Disposal Considerations

Information provided is for unused product only

Recommended method of disposal: It is a hazardous waste, only containers that are approved (eg. By ADR) can be used. Completely emptied containers can be recycled. Treat contaminated packaging in the same way as the substance itself. Dispose of in accordance with Federal, State and local regulations.

14. Transport Information		
U.S Department of Transporta	U.S Department of Transportation Ground (49 CFR):	
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S. (contains fatty acid amidoamine resin)	
Hazard class or division:	9	
Identification number:	UN 3082	
Packaging group:		
Exceptions:	None	
Marine pollutant:	None.	
International Air Transportatio	n (ICAO/IATA):	
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S. (contains fatty acid amidoamine resin)	
Hazard class or division:	9	
Identification number:	UN 3082	
Packaging group:	-DSIUNAL	
Exceptions:	None	
Water Transportation (IMO/IN	IDG):	
Proper Shipping Name:	Environmentally Hazardous Substance, Liquid, N.O.S. (contains fatty acid amidoamine resin)	
Hazard class or division:	9	
Identification number:	UN 3082	
Packaging group:	III	
Marine pollutant:	None.	

# 15. Regulatory Information Chemical Safety Assessment: Chemical safety assessments for substances in this mixture were not carried out Regulations concerning safety, health and environmental regulations / legislation specific for the substance or mixture: Information not available



## SAFETY DATA SHEET



**4 MINUTES STEEL EPOXY** 

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\*\* End of SDS \*\*\*

