

REV : 02
 DATE : 15th Aug 2018

SAFETY DATA SHEET

SL-914 HYBRID HIGH MODULUS MODIFIED PU SEALANT

1. Product & Company Identification

1.1 Product Details

Product name: SL-914 Hybrid High Modulus Modified PU Sealant
 Physical form: Paste
 Odour: Odourless
 Colour: Various
 CAS No.: Mixture

1.2 Company Details

Manufacturer: Silock Technical Inc.
 Address: Nevada 89102 USA

2. Composition / Information on ingredients

| Chemical Name | CAS No. | WT% |
|-----------------------|-----------|------|
| Trimethoxyvinylsilane | 2768-02-7 | 1-5% |

3. Hazard(s) Identification

Hazard Pictogram

None

Signal word: None

GHS Classification:

Not hazardous

Precautionary Statement - Prevention

No precautionary statement

Precautionary Statement - Response

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN - Wash with soap and water.

P305+P351+P338 IF IN EYES - Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do – continue rinsing.

P333+P313 If skin irritation or a rash occurs - Get medical advice/attention.

P337+P313 If eye irritation persist - Get medical advice/attention.

Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement

REV : 02
DATE : 15th Aug 2018

SAFETY DATA SHEET

SL-914 HYBRID HIGH MODULUS MODIFIED PU SEALANT

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact: Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact: Immediately flush with water for several minutes, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.

Unsuitable extinguishing media: Unknown

Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde.

6. Accidental release measures

Methods for cleaning up: Take up mechanically. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust)

Human related safety precautions: Ensure adequate ventilation

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.

Protection against fire/explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control / Personal protection

Ingredients with limited values to be controlled: Not indicated.

Local exhaust: Recommended

General ventilation: Recommended

Hand protection: Suitable protective gloves.

Eye protection: Safety/ protective glasses.

Flammability: Combustible

Note: Until more data is known, exposure levels should be maintained as low as achievable.

REV : 02
 DATE : 15th Aug 2018

SAFETY DATA SHEET

SL-914 HYBRID HIGH MODULUS MODIFIED PU SEALANT

9. Physical and Chemical Properties

| | |
|--------------------------------|-----------------|
| Form: | Paste |
| Specific gravity: | 1.64 ± 0.05 |
| Colour: | Various |
| Viscosity: | Highly viscous |
| Odour: | Odourless |
| %Volatile by volume (25°C): | < 5% |
| Solubility in water: | Insoluble |
| Boiling point: | Not Applicable. |
| Flash point: | > 100°C |
| Ignition temperature: | Not Applicable. |
| Solubility in water(20°C): | Insoluble |
| Vapour pressure: | Not Applicable. |
| Solubility in organic solvent: | Toluene. |

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

| | |
|--|-------------|
| Chemical stability: | Stable |
| Incompatibility (material to be avoid): | None known. |
| Conditions to be avoid: | None known. |
| Dangerous reactions: | None known. |
| Dangerous products of decomposition: | None known. |
| In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides and formaldehyde. | |

11. Toxicological Information

| | |
|---------------------------------------|--|
| Acute toxicity: | Not determined |
| Primary irritant effect, | |
| On the skin: | Irritant for skin and mucous membranes. |
| On the eye: | Irritant effect |
| Sensitization: | Sensitization possible by inhalation. |
| Additional Toxicological information: | Until more data is known, exposure levels should be maintained as low as achievable. |

12. Ecological Information

Complete information not yet available.

REV : 02
DATE : 15th Aug 2018**SAFETY DATA SHEET****SL-914 HYBRID HIGH MODULUS MODIFIED PU SEALANT****13. Disposal considerations**

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of to suitable incineration plant.

14. Transport Information

Proper shipping name: Sealant
Hazard technical name: Not available.
Hazard class: Not available.
No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EU Directives): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

PROFESSIONAL
SOLUTION

*** End of SDS ***