



**SILOCK TECHNICAL INC.**

Address: NEVADA 89102 USA

Website: [www.silock.com.my](http://www.silock.com.my)



REV : 00  
DATE : 19<sup>th</sup> Oct 2012

## TECHNICAL DATA SHEET



### **SL-930 MULTIPURPOSE AWNING CAULK JOINT SEALING & WATERPROOFING COMPOUND (LOW VOC)**



#### **DESCRIPTION:**

**SILOCK** MULTIPURPOSE AWNING CAULK IS ONE PART SEALANT THAT OFFER EXCELLENT ADHESION, OUTSTANDING DURABILITY AND EXCELLENT GUNNABILITY FOR GENERAL SEALING APPLICATION.

#### **FEATURES:**

- ◆ OUTSTANDING DURABILITY
- ◆ ONE PART NO MIXING
- ◆ LOW VOC (VOLATILE ORGANIC COMPOUND)
- ◆ FLEXIBLE ( $\pm 3\%$ )
- ◆ EXCELLENT GUNNABILITY ( $-20^{\circ}\text{C}$  TO  $50^{\circ}\text{C}$ )
- ◆ WEATHER PROOF
- ◆ LOW SHRINKAGE
- ◆ NO SAGGING
- ◆ PRIMERLESS ADHESION TO MOST MATERIALS
- ◆ PAINTABLE AFTER CURED

#### **USES:**

GENERAL JOINT SEALING IN EXTERNAL WALLING, WINDOW AND DOOR FRAMES, ROOFS AND OTHERS.

***WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS***

#### **NOT RECOMMENDED FOR:**

MULTIPURPOSE AWNING CAULK IS NOT SUITABLE FOR HIGH JOINT MOVEMENT SUBSTRATE (MORE THAN  $\pm 3\%$  JOINT MOVEMENT).

#### **COLOUR:**

WHITE, GREY AND BLACK. OTHER COLOURS ARE AVAILABLE UPON REQUEST

## TECHNICAL DATA SHEET



### **SL-930 MULTIPURPOSE AWNING CAULK JOINT SEALING & WATERPROOFING COMPOUND (LOW VOC)**



#### **APPLICATION:**

- ◆ SURFACE MUST BE CLEAN AND DRY.
- ◆ MASK SMOOTH SURFACE TO SIMPLIFY CLEAN UP.
- ◆ USE APPROVED BACK-UP MATERIAL IN JOINT.
- ◆ CUT NOZZLE TO DESIRED SIZE.
- ◆ INSERT CARTRIDGE INTO CAULKING GUN.
- ◆ PUSH SEALANT AHEAD FOR UNIFORM BEAD.
- ◆ TOOL WITHIN 10 MINUTES.
- ◆ CLEAN OFF EXCESS SEALANT WITH MINERAL SPIRIT.

#### **CURING TIME:**

MULTIPURPOSE AWNING CAULK WILL TACK FREE IN APPROXIMATELY 24 HOURS.

#### **SPECIFICATION:**

CURING SYSTEM	OXIDIZING
APPEARANCE	NON-SAGGING PASTE
ODOUR	OLEO-RESINOUS
SPECIFIC GRAVITY	1.60 ± 0.10
MAX. JOINT MOVEMENT	± 3%
SHRINKAGE	5 % APPROX.
TACK FREE TIME	24 HOURS APPROX.
APPLICATION TEMP.	4°C TO 50°C
SERVICE TEMP.	-5°C TO 60°C
SHELF LIFE	12 MONTHS

#### **STORAGE:**

MATERIAL SHOULD BE STORED IN A DRY AND COOL PLACE BETWEEN +5<sup>0</sup>C TO +30<sup>0</sup>C.

#### **CAUTION:**

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

*This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.*